

Important: Always disconnect the power before installing or replacing bulb and before cleaning or other maintenance.

This light should be installed by a licensed electrician

LAMP INSTALLATION AND ASSEMBLY

1. Shut off power to the outlet box. (fig. A)
2. Attach the mounting plate to the outlet box, secure with outlet box screws.
3. Determine the height at which the fixture is to be hung.
Screw stem sections together to achieve desired length.
4. Screw the connector to threaded stem 1.
5. Screw the center stem to the metal ring and threaded stem 2.
6. Screw the stem sections to the connector.
7. Attach canopy to mounting plate with canopy nuts.
8. Make appropriate electrical connections using wire nuts:
 - a. Connect the fixture's live wire (black) to the live outlet box wire.
 - b. Connect the fixture's neutral wire (white) to the neutral outlet box wire.
 - c. Connect fixture's ground wire (green or uncoated) to the ground outlet box wire. If no ground is present in outlet box, connect fixture's ground wire to the mounting plate using the green screw (included).
 - d. Carefully place connections in outlet box.
9. Install candelabra bulbs. (not included)
10. Install shade by fitting the shade pins into the metal ring clips.
11. Screw the finial to the bottom of the fixture body.
12. Restore power to the fixture.

CARE INSTRUCTIONS

Dusting – Use a clean, dry cloth.

Cleaning – To protect the finish, avoid any harsh abrasives or chemicals.

